T-2 Serials Microscope

| Name | Specifications | T-2B | T-2T |
|--------------|--|------|------|
| Viewing | Binocular head, 30° inclined & 360° rotating | • | 0 |
| head | Trinocular head, 30° inclined & 360° rotating | 0 | • |
| Eyepiece | WF10×-18mm Wide-field eyepiece WF10×-18mm | •• | •• |
| | WF16×-13mm Wide-field eyepiece WF16× | 0 | 0 |
| | WF20×-11mm Wide-field eyepiece WF20× | 0 | 0 |
| Nosepiece | Quadruple nosepiece with built-in click stopper | | • |
| | Quintuple nosepiece with built-in click stopper | 0 | 0 |
| Objective | DIN achromatic objective $4\times$, $10\times$, $40\times$ R (spring loaded), | | • |
| | 100×R (oil, spring loaded) | | • |
| | DIN semi-plan achromatic objective $4\times$, $10\times$, $40\times$ R (spring | 0 | 0 |
| | loaded), 100×R (oil, spring loaded) | ► Y | |
| | DIN plan achromatic objective $4\times$, $10\times$, $40\times$ R (spring loaded), | 0 | 0 |
| | 100×R (oil, spring loaded) | | |
| | Infinite achromatic objective $4\times$, $10\times$, $40\times$ R (spring loaded), | 0 | 0 |
| | 100×R (oil, spring loaded) | | |
| Stage | Built-in mechanical stage 132mm×142mm, moving range | • | • |
| | 50mm×76mm with specimen holder, controlled by coaxial knobs | | |
| | at low position on | | |
| Condenser | N.A.1.25 Abbe condenser, iris diaphragm with filter holder | • | • |
| Illumination | Halogen bulb 6V/20W and a power adaptor | • | • |
| | for85V-265V/50Hz. The brightness is adjustable. | | |
| | LED lamps, Ni-Cd rechargeable battery pack, an AC/DC | 0 | 0 |
| | adaptor. The brightness is adjustable. | | |
| Focusing | Coaxial focusing system with built-in tension adjustment and | • | • |
| system | focus stop for preventing damage to slides and objectives | | |
| Optional | DCM35 (350K pixels, USB2.0) digital camera for microscope | 0 | 0 |
| Accessories | DCM130 (1.3M pixels, USB2.0) digital camera for microscope | 0 | 0 |
| | luminium-Alloy Enstrument Case | 0 | 0 |
| | Dark field condenser (wet or dry) | 0 | 0 |
| | Phase contrast set:DIN Plan achromatic objectives 10×, 20×, | 0 | 0 |
| | 40×R, 100×R(oil) condenser; Eyepiece 10× | | |
| Packing | Each set in a foam in a carton | | • |

Note: "•" in the table is standard attachment. "0" is optional accessories.

Design change: To keep pace with technological advances, we have reserved the right to make design modification and changes without notice.

CE ISO9001 ISO14001



Chongqing MIC Technology Co., Ltd Website: <u>www.micscope.com</u> Email: <u>info@micscope.com</u> TEL: +86-13436078184; FAX: +86-23-63913139