

## X-OP1 Fluorescent Microscope

Items	Specification	X-OP12	X-OP14
Eyepiece	WF10×-20 mm	●●	●●
	WF16×-13 mm	○○	○○
	WF10×-20 mm (Reticule 0.1mm)	○	○
Infinity Plan Objective	4×	●	●
	10×	●	●
	20×(S)	●	●
	40×(S)	●	●
	100×(Oil)(S)	●	●
Seidentopf Binocular Head	Inclined 30°,Rotatable 360°, Interpupillary Distance 50-75mm	○	○
Trinocular Head	Inclined 30°, Rotatable 360°, Interpupillary Distance: 55-75mm, Light Distribution: 0:100	●	●
Nosepiece	Quirtuple	●	●
Mechanical Stage	Stage size:190mm×140mm Travel:55mm×78mm Coaxial Coarse and Fine Focusing Knobs	●	●
Condenser	Abbe N.A. 1.25 (Iris Diaphragm)	●	●
Fluorescence Unit	Fluorescence Illuminator (B,G)	●	
	Fluorescence Illuminator (UV, V, B, G)		●
	100W Mercury Bulb House	●	●
	100W Mercury Bulb Power Source	●	●
	Centering Objective	●	●
	110V/220V/100W Mercury Bulb Spare: 1 pc	●	●
	5A Fuse Spare: 1 pc	●	●
Koehler Illumination	6V/20W Halogen Lamp	●	●
2A Fuse	Spare:2 pc	●	●
Filter	Blue	●	●
C-mount	0.3×, 0.5×, 1×	○	○
Adaptor for Digital Camera		○	○

Note: “●” in the table is standard attachment. “○” is optional accessories.

Design change: To keep pace with technological advances, we have reserved the right to make design modification and changes without notice.



Chongqing MIC Technology Co., Ltd  
 Website: [www.micscope.com](http://www.micscope.com)  
 Email: [info@micscope.com](mailto:info@micscope.com)

TEL: +86-13436078184; FAX: +86-23-63913139