

O-P1 Microscope

Items	Specification	O-P1
Eyepiece	WF10×-20 mm	●
	WF10×-20 mm (Reticule 0.1mm)	●
Non-stress Infinity Plan Objective	4×/0.10	●
	10×/0.25	●
	20×/0.45 (S)	●
	40×/0.65 (S)	●
	60×/0.80 (S)	○
Seidentopf Binocular Head	Inclined 30°, Rotatable 360°, Interpupillary Distance: 50-75mm	●
Trinocular Head	Inclined 30°, Rotatable 360°, Interpupillary Distance: 55-75mm, Light Distribution: 0:100	○
Nosepiece	Quintuple (Adjustable independence)	●
Polarizing Unit	Rotatable 360°(Module Type, Can Be Locked)	●
Bertrand Lens	Inbuilt, Center Adjustable	●
λSlip	First Class Red	●
λ/4 Slip		●
Quartz Wedge	(I -IV Class)	●
Revolving Round Stage	Rotatable 360°, Center Adjustable, Division 1°, Vernier division 6'	●
Polarizing Attached Mechanical Stage		○
Condenser	Abbe N.A. 1.25, Non-stress	●
Polarizing Unit with Scale	Rotatable 360°, Can Be Locked	●
Koehler Illumination	6V/20W Halogen Lamp	●
2 A Fuse	Spare: 1 pc	●
Filter	Blue	●
	Amber	○
	Green	○
	Neutral	○
C-mount	0.5×, 1×	○
Adaptor for Digital Camera		○

Note: “●” in the table is standard attachment. “○” is optional accessories.

Design change: To keep pace with technological advances, we have reserved the right to make design modification and changes without notice.



Joy with your eyes

Chongqing MIC Technology Co., Ltd

Website: www.micscope.com

Email: info@micscope.com

TEL: +86-13436078184; FAX: +86-23-63913139